



# POWER REPAIR

## SUPER STRONG DUCT TAPE WITH PE COATING FOR UNIVERSAL USE



### TECHNICAL SPECIFICATIONS

Carrier type:	LDPE
Chemical base:	Synthetic rubber
Initial tack:	High
Minimum temperature resistance:	-10 °C
Maximum temperature resistance:	75 °C
Peel adhesion:	SS 18 N/25mm
Rolling ball tack:	<3 cm
Tensile Strength (N/25 mm) approx.:	95 N/25 mm
Thickness (mm):	0.195 mm
Colour:	Grey

### STORAGE CONDITIONS

Store in a cool, dry place out of direct sunlight.

### PRODUCT DESCRIPTION

Super strong duct tape with PE coating and extra initial high-tack for repairing, strengthening, sealing, connecting and protecting, indoor and outdoor.

### FIELD OF APPLICATION

Suitable for repairing, strengthening, sealing, connecting and protecting. Super strong duct tape for a universal use. For indoor and outdoor applications. It adheres on many synthetic materials (e.g. PVC, ABS), glass, metal, textile, wood, stone.

### PROPERTIES

- Super strong
- Extra initial high tack
- Universal
- Indoor and Outdoor
- Temperature resistant
- Waterproof
- UV resistant
- Can be torn off manually

### PREPARATION

**Surface Requirements:** The surface must be clean, dry and free of dust and grease.

### APPLICATION

#### Directions for use:

Stick and press well the tape onto the object without touching the adhesive as this reduces the adhesive strength.

**Stains/residue:** Remove possible tape residue with white spirit.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.